

Rec'd PCT/PTO

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

10/501309

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 September 2003 (18.09.2003)

PCT

(10) International Publication Number
WO 03/076483 A2

(51) International Patent Classification⁷: C08F 210/02,
C08J 5/18, D01F 6/32, D01D 5/11

(US). SAMUELS, Sam, L. [US/US]; 34 Pelham Drive,
Landenberg, PA 19350 (US). SIEMIONKO, Roger, K.
[US/US]; 14107 Dorsetshire Court, Midlothian, VA 23113
(US).

(21) International Application Number: PCT/US03/07026

(22) International Filing Date: 7 March 2003 (07.03.2003)

(74) Agent: DOBSON, Kevin, S.; E.I. Dupont De Nemours
and Company, Legal Patent Records Center, 4417 Lan-
caster Pike, WILMINGTON, DE 19805 (US).

(25) Filing Language: English

(26) Publication Language: English

(81) Designated States (*national*): CA, JP, US.

(30) Priority Data:
60/362,703 7 March 2002 (07.03.2002) US

(84) Designated States (*regional*): European patent (AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,
IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(71) Applicant (*for all designated States except US*): E.I. DU
PONT DE NEMOURS AND COMPANY [US/US]; 1007
Market Street, Wilmington, DE 19898 (US).

Published:

— *without international search report and to be republished
upon receipt of that report*

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): CHOU, Richard,
T. [US/US]; 173 Thompson Drive, Hockessin, DE 19707

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: FLUORINE-CONTAINING ETHYLENE COPOLYMERS

(57) **Abstract:** The present invention is a fluorine containing ethylene copolymer (FCEC) obtained by the copolymerization of ethylene with suitable fluorine-containing comonomer compounds, wherein the fluorine-containing comonomer compound is present at a concentration of up to 40% by weight, based on the total weight of the ethylene copolymer. FCEC described herein can be useful in a variety of applications, for example: as a release resin in low surface energy release films; as melt blown fibers; in composite or multilayer structures as a low surface energy outer layer; as microporous membranes; as flashspun plexifilamentary products; and as melt spun fibrous products.

WO 03/076483 A2